

AGS Secure Geocode Service URL

Add a New Monitoring Point

Select Type

AGS GeoCode Service URL

Monitor Name

Monitor Description

Server Name

Service Name

URL-Complete

Create Monitor Point

The AGS Secure Geocode Service URL monitoring point checks a Secure ArcGIS Server Geocode service to see if it returns an x,y location for a valid address.

The parameters that are unique to the AGS Secure Geocode Service URL include:

Server Name	DNS name of server where AGS Geocode service is located
Service Name	Name of the geocode service on an ArcGIS Server. If service is under a folder, folder/service is needed.
userID	ArcGIS Server Admin user ID using either Windows or ArcGIS Server Security
UserPW	ArcGIS Server Admin user password
URL-Complete	This parameter can be retrieved from using Arc Map, or better, the REST interface service and entering the parameters to test. Copy the parameters from the 'URL' address bar of the Browser.

For non-secured AGS Geocode Service URLs, refer to the [AGS Geocode Service URL](#) monitoring point script.

Retrieving the URL-Complete parameter from the REST service is a several step process.

Step 1.1: Open your Internet browser and enter the URL for your ArcGIS® Rest Services

Example:

http://YourServerName/ArcGIS/Rest/Services

Step 1.2: Select a Geocoding Service from your list of services

Folder: /

Current Version: 9.31

View Footprints In: [Google Ea](#)

Folders:

- **Your Folders**

Services:

- 
- Your List of
ArcGIS Services**

**Your List of
ArcGIS Services**

Step 1.3: In the bottom left of the browser screen, locate "Supported Operations"

Click on **[Find Address Candidates]**

Supported Interfaces: [REST](#) [SOAP](#)

Supported Operations: [Find Address C...](#)

Step 1.4: Enter a valid address in the **Address** field

Note: Your GeoCoder form view may vary from the image at the right depending on the Locator style

Find Address Candidates:

Address:

Zone:

Return Fields (*Comma Separated*):

Format: 

Step 1.5: Select *JSON* from the **Format** drop down box

Find Address Candidates:

Address:

Zone:

Return Fields (Comma Separated):

Format: 

Step 1.6: Click on **[Find]**

Find Address Candidates:

Address:

Zone:

Return Fields (Comma Separated):

Format:



Step 1.7: Verify that valid data is returned

Note: If the data is not valid, the browser will display an empty page without an x, y coordinate. If this happens, locate a valid address and return to Step 1.4.

```
{
  "candidates" : [
    {
      "address" : "123 Main Street",
      "location" : {
        "x" : 6022726.86,
        "y" : 2165763.09
      },
      "score" : 37,
      "attributes" : {
      }
    },
    {
      "address" : "123 Main Street",
      "location" : {

```

Step 1.8: Copy the entire URL in the browser address bar

Example Complete URL

<http://ServerName/ArcGIS/rest/services/CompositeLocator/GeocodeServer/findAddressCandidates?Address=123+Main+Street&Zone=&outFields=&f=pjson>

Step 2: Paste the complete URL into the URL-Complete field provided

Step 3: Click the **[Create Monitor Point]** button

Article ID: 280

Last updated: 14 Aug, 2018

Revision: 7

GeoSystems Monitor Enterprise -> Product Guide v4.0 -> Monitor Point Types & Parameters -> AGS Secure Geocode Service URL

<http://www.vestra-docs.com/index.php?View=entry&EntryID=280>