

# Oracle SDE List Tables

Add a New Monitoring Point

Select Type

Oracle SDE List Tables

Monitor Name

Monitor Description

Server Name

Svr NM w/Listener

userID

Encrypt

userPW

Encrypt

Rpt-DSN:Usr:Pwd

Encrypt

Opt-UserSchema

Create Monitor Point

The **Oracle SDE List Tables** monitoring point is designed to work together with the **Oracle SDE Usage** monitoring point. Both are needed to generate the data required to support SDE Usage reporting.

The Oracle SDE List Tables check runs once a week based on a time stamp stored in the GeoMonitor database. This check is designed to report on feature datasets, feature classes and tables in an Oracle SDE instance. This list includes feature classes and tables that are unused for SDE Usage reporting. The Oracle SDE Usage check is generally run on a daily basis and reports on feature classes and tables that are open. A more detailed description of the [Oracle SDE Usage check](#) is provided in a later section.

**Note:** If you are using Microsoft SQL Server / SQL Server Express, follow the instructions in [Setting Up Microsoft SQL Server / SQL Server Express](#).

If you are not sure where your Usage information is being stored, you can consult the “About” dialog on the main application window.

This check needs an Oracle (32Bit) client that customer provides which is installed locally and configured to use the ORACLE\_HOME environment variable is set and that the system PATH is set to the folder where the Oracle client is installed.

**Note:** If you are using Microsoft SQL Server / SQL Server Express, follow the instructions in [Setting Up Microsoft SQL Server / SQL Server Express](#).

The parameters that are unique to the Oracle SDE List Tables include:

Server Name	Domain name of Server (or IP address)
Server Nm w/Listener	Server name, port and listener to connect to the Oracle DB <b>Example:</b> voracle10g:1521/vector <b>(Must be identical for this check and U</b>
userID	Oracle user ID with access to the Oracle Table <b>Note:</b> userID should be entered as encrypted information
userPW	Oracle user PW for access to the Oracle Table <b>Note:</b> userPW should be entered as encrypted information
Rpt-DSN:User:Pwd	Needed only if using RDBMS to store usage information – string must include YourODBC_ConnectionName:UserID:UserPW <b>Note:</b> Rpt-DSN:User:Pwd should be entered as encrypted information
Opt-User Schema	Defaults to SDE. Enter User Schema if needed. Compatible with 12c pluggab

---

Article ID: 295

Last updated: 21 Aug, 2018

Revision: 16

GeoSystems Monitor Enterprise -> Product Guide v4.0 -> Monitor Point Types & Parameters -> Oracle SDE List Tables

<http://www.vestra-docs.com/index.php?View=entry&EntryID=295>