

## Oracle SDE List Tables 9.x

### Add a New Monitoring Point ✕

Select Type

Oracle SDE List Tables 9.x ▼

Monitor Name

Monitor Description

---

Server Name

Svr NM w/Listener

userID

userPW

Rpt-DSN:Usr.Pwd

Opt-UserSchema

**Create Monitor Point**

The Oracle SDE List Tables 9x monitoring point is designed to work together with the Oracle SDE Usage check to generate SDE Usage reporting. It is recommended that these two checks be placed together in a GeoMonitor Server to generate the data required to support SDE Usage reporting.

The Oracle SDE List Tables 9x check runs once a week based on a time stamp stored in the GeoMonitor database. It checks the Oracle SDE (version 9.x) geodatabase feature datasets, feature classes and tables in an Oracle SDE instance. This list includes feature datasets, feature classes and tables that are unused for SDE Usage reporting. The Oracle SDE Usage check is generated for feature datasets, feature classes and tables that are open. A more detailed description of the [Oracle SDE Usage check](#) is provided in the Oracle SDE Usage check documentation.

If you are not sure where your Usage information is being stored, you can consult the “About” dialog on the Oracle SDE Usage check.

This check needs an Oracle (32Bit) client that customer provides which is installed locally and configured to use the ORACLE\_HOME environment variable is set and that the system PATH is set to the folder where the Oracle client is installed.

**Note:** If you are using Microsoft SQL Server / SQL Server Express, follow the instructions in [Setting Up Microsoft SQL Server / SQL Server Express](#).

The parameters that are unique to the Oracle SDE List Tables 9x include:

Server Name	Domain name of SDE Server (or IP address)
Server Nm w/Listener	Server name, port and listener to connect to the Oracle DB <b>Example:</b> voracle10g:1521/vector <b>(Must be identical for this check and</b>
userID	Oracle user ID with access to the Oracle Table <b>Note:</b> userID should be entered as encrypted information
userPW	Oracle user PW for access to the Oracle Table <b>Note:</b> userPW should be entered as encrypted information
Rpt-DSN:User:Pwd	Needed only if using RDBMS to store usage information - string must include YourODBC_ConnectionName:UserID:UserPW <b>Note:</b> Rpt-DSN:User:Pwd should be entered as encrypted information
Opt-User Schema	<b>(Optional)</b> Leave blank for Oracle SDE

---

Article ID: 296

Last updated: 21 Aug, 2018

Revision: 7

GeoSystems Monitor Enterprise -> Product Guide v4.0 -> Monitor Point Types & Parameters -> Oracle SDE List Tables  
9.x

<http://www.vestra-docs.com/index.php?View=entry&EntryID=296>